

Sliding Doors



Manufactured by

The doors are manufactured by Flexicold at their Bordon based factory

Types of Sliding Doors

- Manually operated high temperature.
- Manually operated low temperature.
- Electrically operated high temperature.
- Electrically operated low temperature.

Track options

- Fermod manually operated
2000 series, 3000 series, 4000 series, 7000 series

Door Leaf

- The door leaves can be manufactured timber less.
- Standard door thickness is 100mm

● **Insulation core:** -

Mineral Fibre
Polyisocyanurate.

● **Finish:** -

White food safe laminate
Coloured HP 200
Coloured PVF2
Flat Glasbord
Embossed Glasbord
Stainless Steel

DH Holdings Ltd t/a Flexicold Manufacturing

Unit 19 & 20, Old Station Way, Bordon Hants, GU35 9HH

Tel: 01420 473229 **Fax:** 01420 478474 **Email:** sales@flexicold.co.uk

Company reg no: 0306 7319 VAT reg no 744 5601 35



Door Frames

- Frames would be manufactured with a timber core or an exterior grade plywood core.
- The frames would be encased in
White food safe laminate
Coloured HP200
Coloured PVF2
Stainless steel
- The frames would be securely fixed to the insulated panelling by means of nylon bolts.
- The frames can be designed to fit into a brick opening or into an opening formed in the metal cladding of a building.

Optional Extras

The electrically operated conversion kit can be fitted to the track when door fitted or if the budget don't stretch can be fitted at a later date.

Electrically operated tracks can be supplied with the following

- Standard – Pull cords and push buttons
- Radar operated
- Pressure pad operations
- Locks
- Electrical connections: -

We would fit the automatic conversion kit to the track, but we leave loose for your electrician to install.

Control panel

Push buttons

Pull cords

All interconnecting wiring and connections

Low Temperature doors

- The doors would come complete with low voltage heater tapes and transformer.
- To install the threshold heater a recess must be provided by the main contractor in the doorway and adjacent to main freezer recess
- Size is Clear opening width of door opening x 300mm x the depth of main recess.