

Model		XJW02LAY	XJW03LAY	XJW04LAY	XJW05LAY	XJW06LAY	XJW08LAY	XJW09LAY	XJW10LAY	
Temperature (°C)		-15°C~-18°C								
Refrigerant		R404A								
Power supply		380V/50HZ/3PH								
Compr	Type	Scroll								
	Model	ZB15KQE	ZB21KQE	ZB30KQE	ZB38KQE	ZB45KQE	ZB58KQE	ZB66KQE	ZB76KQE	
	Number	1	1	1	1	1	1	1	1	
Cond	Fan number	1	1	1	2	2	2	4	4	
	Air flow (m ³ /h)	3200	3200	4600	6400	6400	9200	12800	12800	
	Fan input (W)	110	110	150	110×2	110×2	150×2	110×4	110×4	
Capacity and input	Evap -15°C	Cap (W)	2080	3350	4500	5650	6700	8500	10600	12500
		input (W)	2180	2830	3790	4680	5350	7350	7850	9200
	Evap -20°C	Cap (W)	1560	2650	3550	4500	5300	6200	8350	10300
		input (W)	2260	2830	3810	4670	5350	7450	7850	9100
	Evap -25°C	Cap (W)	1080	2070	2770	3500	4150	4800	6960	8980
		input (W)	2320	2830	3820	4650	5300	7050	7250	8500
Pipe	Gas pipe (mm)	φ 22	φ 22	φ 22	φ 22	φ 22	φ 28	φ 28	φ 28	
	Liquid pipe (mm)	φ 12	φ 12	φ 12	φ 12	φ 12	φ 16	φ 16	φ 16	
Weight (kg)		80	88	100	138	140	165	233	238	
Over all	A (mm)	1100	1100	1100	1100	1100	1100	1700	1700	
	B (mm)	550	550	550	550	550	550	550	550	
	C (mm)	635	635	1238	1238	1238	1238	1288	1288	

Condensing temp.: 50°C、Suction super heat: 10K

3. Overall dimensions

